


CPR (UE) n°305/11
C_{ca} - s3, d1, a3

Regolamento Prodotti da Costruzione/Construction Products Regulation
Classe conforme norme EN 50575:2014 + A1:2016 e EN 13501-6:2014
Class according to standards EN 50575:2014 + A1:2016 and EN 13501-6:2014

DoP n°1022/17

CEI 20-13 - CEI UNEL 35318
CEI EN 60332-1-2
2014/35/UE

Costruzione e requisiti/Construction and specifications
Propagazione fiamma/Flame propagation
Direttiva Bassa Tensione/Low Voltage Directive



FG16R16 REPERO® - Cca-s3,d1,a3



DESCRIZIONE

Cavo unipolare per energia isolato in gomma etilpropilenica ad alto modulo di qualità G16, sotto guaina di PVC, con particolari caratteristiche di reazione al fuoco e rispondente al Regolamento Prodotti da Costruzione (CPR).

Conduttore

Corde flessibile di rame rosso ricotto, classe 5

Isolante

Miscela di gomma etilpropilenica ad alto modulo di qualità G16

Guaina esterna

Miscela di PVC di qualità R16

Colore anime

Normativa HD 308

Colore guaina

Grigio

Marcatura a inchiostro

BALDASSARI CAVI REPERO® FG16R16 0,6/1 kV (sez)
Cca-s3,d1,a3 IEMMEQU EFP (anno) (m) (tracciabilità)

CARATTERISTICHE TECNICHE

Tensione nominale U_o/U: 0,6/1 kV

Temperatura massima di esercizio: 90°C

Temperatura minima di esercizio: -15°C
(in assenza di sollecitazioni meccaniche)

Temperatura minima di posa: 0°C

Temperatura massima di corto circuito:
250°C fino alla sezione 240 mm², oltre 220°C

Sforzo massimo di trazione: 50 N/mm²

Raggio minimo di curvatura: 4 volte il diametro esterno massimo

Condizioni di impiego

Cavi adatti all'alimentazione elettrica in costruzioni ed altre opere di ingegneria civile con l'obiettivo di limitare la produzione e la diffusione di fuoco e di fumo. Per impiego all'interno in locali anche bagnati o all'esterno. Adatto per posa fissa su murature e strutture metalliche in aria libera, in tubo o canaletta o sistemi similari. Ammessa anche la posa interrata. (rif. CEI 20-67)

DESCRIPTION

Single-core power cable HEPR insulated (G16 quality), PVC sheathed, with special fire reaction characteristics according to Construction Products Regulation (CPR).

Conductor

Plain copper flexible wire, class 5

Insulation

Rubber HEPR compound, G16 quality

Outer sheath

PVC compound, R16 quality

Cores colour

HD 308 Standard

Sheath colour

Grey

Inkjet marking

BALDASSARI CAVI REPERO® FG16R16 0,6/1 kV (section)
Cca-s3,d1,a3 IEMMEQU EFP (year) (m) (traceability)

TECHNICAL CHARACTERISTICS

Nominal voltage U_o/U: 0,6/1 kV

Maximum operating temperature: 90°C

Minimum operating temperature: -15°C
(without mechanical stress)

Minimum installation temperature: 0°C

Maximum short circuit temperature:
250°C up to 240 mm² section, over 220°C

Maximum tensile stress: 50 N/mm²

Minimum bending radius: 4 x maximum external diameter

Use and installation

Cables suitable for electrical power system in constructions and other civil engineering works in order to limit fire spread and smoke emission. Suitable to be used indoor or outdoor, even in wet environments; it can be fixed on walls and/or metal structures, free in air, inside pipes or similar systems. Suitable also for laying underground. (ref. CEI 20-67)



Formazione	Ø indicativo conduttore	Spessore medio isolante	Spessore medio guaina	Ø indicativo produzione	Peso indicativo cavo	Resistenza elettrica max a 20°C	Portata di corrente Current rating	
Formation	Approx. conductor Ø	Average insulation thickness	Average sheath thickness	Approx. production Ø	Approx. cable weight	Max. electrical resistance at 20°C	In tubo in aria In pipe in air 30°C	Interrato Underground 20°C
n° x mm ²	mm	mm	mm	mm	kg/km	ohm/km	A	A
1 x 1,5	1,6	0,7	1,4	6,0	50	13,3	20	21
1 x 2,5	1,9	0,7	1,4	6,3	60	7,98	28	27
1 x 4	2,5	0,7	1,4	6,9	78	4,95	37	35
1 x 6	3,0	0,7	1,4	7,4	98	3,30	48	44
1 x 10	4,0	0,7	1,4	8,4	144	1,91	66	59
1 x 16	5,0	0,7	1,4	9,3	197	1,21	88	77
1 x 25	6,2	0,9	1,4	11,0	295	0,780	117	100
1 x 35	7,6	0,9	1,4	12,1	385	0,554	144	121
1 x 50	8,9	1,0	1,4	13,9	525	0,386	175	150
1 x 70	10,5	1,1	1,4	15,4	715	0,272	222	184
1 x 95	12,5	1,1	1,5	17,3	935	0,206	269	217
1 x 120	13,7	1,2	1,5	18,9	1160	0,161	312	259
1 x 150	15,0	1,4	1,6	21,2	1470	0,129	355	287
1 x 185	17,7	1,6	1,6	24,4	1780	0,106	417	323
1 x 240	19,9	1,7	1,7	27,5	2300	0,0801	490	379
1 x 300	22,4	1,8	1,8	30,5	2900	0,0641	-	429
1 x 400	24,8	2,0	1,9	33,1	3500	0,0486	-	500

N.B. Il coefficiente di resistività termica del terreno preso a riferimento per il calcolo della portata dei cavi interrati è di 1,5 K.m/W, profondità di posa 0,8 m. Calcolo della portata di corrente eseguito considerando un circuito con 3 conduttori attivi (per cavi unipolari), eseguito considerando 2 conduttori attivi per cavi a 2 anime e 3 conduttori attivi per le altre formazioni.

N.B. The thermal resistivity coefficient used as a reference for the calculation of the underground cables current rating is 1,5 K.m/W, 0,8 m installation depth. Calculation of current rating performed considering a circuit with 3 loaded conductors (for single-core cables); performed considering 2 core cables and 3 loaded conductors for other formations.